

FORK COMPATIBILITY LIST - PROGUARD BOLT ON MUDGUARDS

*** ALWAYS CHECK BOTTOM OUT CLEARANCE BEFORE USE AS MANUFACTURERS ARE CHANGING THEIR DESIGNS CONSTANTLY ***

CHECK YOUR FORK COMPLIES WITH THESE 3 THINGS:

1. YOUR FORK MUST HAVE THREADED HOLES - SOME OF FORKS COME WITHOUT THREADED HOLES
2. MINIMUM OFFSET IS 44MM
3. FORK WHEEL SIZE IS 27.5" OR 29"

KEY

COMPATIBLE	➡	ANY NUMBER SHOWN RELATES TO THE ADAPTER REQUIRED (SEE ADAPTER LIST AT BOTTOM)
MAY BE COMPATIBLE	➡	SEE NOTES - MAY BE MODEL SPECIFIC OR NEED MODIFICATION - NUMBER SHOWS ADAPTER BRACKET ALSO REQUIRED - SEE ADAPTERS
UNKNOWN / NOT TESTED	➡	COMPATIBILITY UNKNOWN / NOT TESTED
NOT COMPATIBLE	➡	CABLE TIE PROGUARDS ARE COMPATIBLE WITH MOST CONVENTIONAL FORKS (VELCRO PACKS ALSO AVAILABLE)
V1 ORIGINAL BOLT ON V1	➡	SIZES AVAILABLE - MINI / STANDARD
V2 NEW BOLT ON V2	➡	SIZES AVAILABLE - MINI / STANDARD / MAX PROTECTION (NOTE: MAX PROTECTION NOT RECOMMENDED FOR AGGRESSIVE / DH RIDING)

MAKE / MODEL	*MODEL YEAR (MY)							NOTES
	2019	2020	2021	2022	2023	2024	2025	
FOX								
32								
34 NON STEP-CAST				1	1	1	1	V2 ONLY - Hollow fork brace versions with no supports need an adapter bracket (see below)
34 STEP-CAST				2	2	2	2	V1 & V2 (V2 tight fit) - Hollow fork brace versions with no supports need an adapter bracket (see below)
36			3	3	3	3	3	MY2021 needs Fox 36 Stability Bracket (supplied) - Must check earlier models for bottom out clearance
38								Use the Tilt Bracket in the pack to raise the front end
40	4	4						MINI SIZE ONLY - Not recommended to use the STD or MAX size due to poor rubber contact (stability issues)
49	4	4						MINI SIZE ONLY - Not recommended to use the STD or MAX size due to poor rubber contact (stability issues)
AWL 29"								
MARZOCCHI								
BOMBER Z1								
BOMBER Z2								Z2 forks don't come with any threaded holes - if you decide to add helicoil threads then it will fit
BOMBER 58								
BOMBER DJ								
ROCKSHOX								
RECON GOLD								
RECON SILVER								BOOST HUB FORKS ONLY - Use the M6 bolt for the centre threaded hole only
JUDY GOLD								
JUDY SILVER								If it has threaded holes, use the M6 bolt for the centre threaded hole only (tight fit)
BLUTO								No threaded holes
REBA								If it has threaded holes, use the M6 bolt for the centre threaded hole only

AXON32/34/35									
AXON36/38									
ZERON35/36									
RAIDON32/34									
XCR32									Use the M6 bolt for the centre threaded hole only
XCR34									May need supplied tilt bracket to raise the front
XCM									Use M6 bolt for centre threaded hole
XCM32									
XCM34									Use M6 bolt for centre threaded hole
XCT					13	13			Needs SR SUNTOUR Sleeve Pack
XCE 27.5"									May need to use supplied Tilt Bracket to lower front
XFUSION	<2020	2020	2021	2022	2023	2024	2025	NOTES	
RV-1 HLR / METRIC									Not enough tyre clearance
TRACE 34									OEM fork
TRACE 36		11	11	11	11	11			
SWEEP / SLANT									No threaded holes
MCQUEEN									
REVEL X									Not compatible with any upside down fork
SLIDE 32MM/ 34MM									No threaded holes
VELVET									No threaded holes
RC32									No threaded holes
MIG 27.5 32		11	11	11	11	11			Bolt On v1 use just M6 centre bolt to secure / for v2 use Adapter Bracket 11 detailed below
EXT - EXTREME SHOX	<2020	2020	2021	2022	2023	2024	2025	NOTES	
ERA V1		11	11	11	11	11			Bolt on v1 - screw bolts through slots to cut into plastic first / check bottom out - may need to modify see how below
ERA V2 & V2.1				11	11	11			Bolt on v1 - screw bolts through slots to cut into plastic first / check bottom out - may need to modify see how below
OTHERS FORKS NOT LISTED ABOVE								NOTES	
CANE CREEK									Adapter was designed but there was insufficient tyre clearance
BRIGHT RACING									Doesn't fit upside-down forks
FORMULA									2023 Earlier - No threaded holes in rear of fork brace
RST SELVA									
MANITOU									Doesn't fit upside-down or reverse arch forks
BOS									No threaded holes in rear of fork brace
MRP									No threaded holes in rear of fork brace
DT SWISS									Adapter was designed but there was insufficient stability and clearance
TRUST									No threaded holes or rear fork brace
INTEND / WREN									Doesn't fit upside-down forks
* The year your fork or bike was purchased brand new isn't always the model year (MY) of your fork - older model year forks are sold on brand new bikes so check first									
EVERY EFFORT IS MADE TO ENSURE THE ABOVE DETAILS ARE CORRECT, THERE ARE HUNDREDS OF FORKS / VARIATIONS SO PLEASE ADVISE IF NOT CORRECT									

PROGUARD ADAPTER BRACKET DETAILS

No	PRODUCT CODE	PRODUCT NAME	MUDGUARD	PRODUCT / DESCRIPTION
1	PGBOF34	FOX 34 (HOLLOW BRACE) NON STEP-CAST ADAPTER BRACKET	v2	FOX 34 (HOLLOW BRACE) NON STEP-CAST ADAPTER BRACKET - NON STEP-CAST version only
2	PGBOF34S	FOX 34 (HOLLOW BRACE) STEP-CAST ADAPTER BRACKET	v1 & v2	FOX 34 (HOLLOW BRACE) STEP-CAST ADAPTER BRACKET - STEP-CAST version only
3	PGBOF36	FOX 36 STABILITY BRACKET	v1 & v2	FOX 36 STABILITY BRACKET (supplied with mudguard)
4	PGBOF40	FOX 40/49 ADPATER BRACKET (49 v2 ONLY) 26" & 27.5"	v1 & v2	FOX 40/49 ADPATER BRACKET 26" & 27.5" forks only - Fox 49 use v2 ONLY
5	PGBOZD	ROCKSHOX ZEB / DOMAIN ADAPTER BRACKET	v2	ROCKSHOX ZEB / DOMAIN ADAPTER BRACKET (includes bolt)
6	PGBORXF34	OHLINS RXF34 FITTING KIT	v1 & v2	OHLINS RXF34 FITTING KIT required (includes spacer and bolt)
7	PGOSB	OHLINS RXF36 / DH38 STABILITY BRACKET	v1	v1 Ohlins STABILITY BRACKET for RXF36 / DH38 (MINI ONLY for DH38 fit in highest position)
7a	PGOSB2	OHLINS RXF36 / DH38 STABILITY BRACKET	v2	v2 Ohlins STABILITY BRACKET for RXF36 / DH38 (MINI ONLY for DH38 fit in highest position)
8	PGBORXF38	OHLINS RXF38 STABILITY BRACKET	v2	OHLINS RXF38 STABILITY BRACKET
9	PGBODVOB	DVO DIAMOND M4 x 14mm / Washer	v1 & v2	DVO DIAMOND M4 x 14mm / Washer
10	PGBODVO	DVO ONYX SC ADAPTER BRACKET & BOLT/WASHER	v1 & v2	DVO ONYX SC ADAPTER BRACKET & BOLT/WASHER (includes bolt / washer)
11	PGERAXFT36	EXT ERA/XFUSION TRACE36 ADAPTER BRACKET	v1 & v2	v1 & v2 EXT ERA / v1 & v2 - XFUSION TRACE36 - MIG 27.5 32 only needs bracket for v2
12	PGBOLP	ROCKSHOX LYRIK / PIKE ADAPTER BRACKET	v2	For Model Year (MY) 2022 Lyrik / Pike
13	PGBOSP	SR SUNTOUR - FITTING KIT (OPEN HOLE)	v1 & v2	For straight through UNTHREADED centre holes

MODIFYING THE ORIGINAL BOLT ON V1

Some fork versions (RXF38) have extra large CSU crown that won't clear the bolt on v1 bracket on bottoming, however you still may be able to modify it to fit. You can see if your CSU is the standard or extra large version by simply measuring the widest point of the round top crown and checking the details below:



1. STANDARD CSU CROWN = Approximately 60mm
2. EXTRA LARGE CSU CROWN = Approximately 66mm -70mm

NOTE: You can check your bottom out clearance by removing the air from your fork and slowly depressing the fork to see if it clears the bracket

If yours is the XL version then you need to either buy the new bolt on v2 (which doesn't need modifying) or modify the bracket on your v1 mudguard for more bottom out clearance, you will still need the appropriate adapter bracket stated for you fork.
See how to modify below (WARNING - ADULTS ONLY):



WARNING ADULTS ONLY: BE CAREFUL NOT TO SLIP AND PUNCTURE THE MUDGUARD OR HURT YOURSELF

MODEL YEAR 2022 Fox 34

If you have the new MY22 Fox 34 fork with the hollowed out fork brace with no support struts at the back (like the picture below), then you will need an adapter bracket, see compatibility below:

V2 COMPATIBLE WITH THE STEP-CAST VERSION & NORMAL NON-STEP CAST VERSION

V1 COMPATIBLE WITH THE STEP-CAST VERSION ONLY

EXAMPLE - HOLLOW BRACE WITHOUT SUPPORTS:



If you have a fork brace WITH centre support struts in the rear of the brace to support a mudguard, it will fit without an additional adapter bracket

EXAMPLE - MY21 FOX FORK BRACES WITH SUPPORTS BELOW:



EXAMPLE - FOX 34 STEP-CAST BELOW:



EXAMPLE - MY20 (or earlier) FOX FORK BRACE WITH SUPPORTS BELOW:

